

SuperFinisher™



NF565/16

16GA. Brad Nailer

Drives 32 to 65mm (1-1/4" to 2-1/2") length Brad nails

FEATURES

- **Lightweight-only 1.6kg & Slim body**
Compact and well balanced body. Easily reaches tight spots.
- **Selectable fire mechanism**
The tool can be contact or single fired with switch lever.



- **Dial adjustable depth control**
Dial depth control requires no special tools.

- **Easy jam clearance system**



- **Belt hook**

- **Easy twist adjustable exhaust deflector**
Exhaust air can easily be diverted 360° away from user without any tool.



APPLICATIONS

- Door and window casings ● Plywood, decorative boards, and other interior finish works ● Panel assembly and mouldings
- Sub flooring ● Furniture assembly, case back fastening, blind pinning and other finishing work ● Cabinet assembly



Comes with a Plastic carry case

TOOL SPECIFICATIONS

PRODUCT NO.	NF565/16
DIMENSIONS	285(H)×96(W)×297(L)mm (11-3/8"×3-13/16"×11-11/16")
WEIGHT	1.6kg (3.5lbs)
RECOMMENDED OPERATING PRESSURE	5 to 7 bar (70 to 100 p.s.i.)
LOADING CAPACITY	100 brads
AIR CONSUMPTION	1.3ℓ (0.045ft³) at 6.9 bar operating pressure
TECHNICAL DATA NOISE	A-weighted single-event sound power level LWA, 1s, d 93.3dB A-weighted single-event sound pressure level LpA, 1s, d 84.2dB
VIBRATION	3.5m/s²
Vibration characteristic value	These values are determined and documented in accordance to EN12549:1999 and ISO 8662-11

FASTENERS APPLICABLE

16 Ga. Brad Nails



Length
32mm
(1-1/4")
to
65mm
(2-1/2")

Thickness
1.4mm
(.055")



The specifications and design of the products in this catalogue will be subject to change without advance notice due to our continuous efforts to improve the quality of our products



The Netherlands
Camerastraat 19, 1322 BB Almere
Tel: +31-(0)36-546-9669 FAX: +31-(0)36-536-3985
Web: www.max-europe.com
e-mail: sales@max-europe.com

Dealer: