uperfinisher.



NF665/15

Drives 32 to 65mm(1-1/4" to 2-1/2") length Finish nails

FEATURES

- ■Lightweight-only 1.8kg & Slim body Compact and well balanced body. Easily reaches tight spots.
- Selectable fire mechanism The tool can be contact or single fired with switch lever.







Dial adjustable depth control

Dial depth control requires no special tools.

■Easy jam clearance system





Belt hook

Easy twist adjustable exhaust deflector

Exhaust air can easily be diverted 360° away from user without any tool.



APPLICATIONS

- Door and window casings
 Plywood, decorative boards, and other interior finish works
 Panel assembly and mouldings
- Sub flooring
 Furniture assembly, case back fastening, blind pinning and other finishing work ●Cabinet assembly







The specifications and design of the products in this catalogue will be subject to change without advance notice due to our continuous efforts to improve the quality of our products

(15GA. Angled Finish Nailer) Comes with a **Plastic** carry case

TOOL SPECIFICATIONS

| PRODUCT NO. | | NF665/15 | |
|---|--|--|--|
| DIMENSIONS | | 322(H)×94(W)×322(L)mm (12-5/8"×3-3/16"×12-5/8") | |
| WEIGHT | | 1.8kg (3.97lbs) | |
| RECOMMENDED OPERATING PRESSURE | | 5 to 7 bar (70 to 100 p.s.i.) | |
| LOADING CAPACITY | | 100 brads | |
| AIR CONSUMPTION | | 2.74(0.096ft3) at 7 bar operating pressure | |
| TECHNICAL DATA NOISE | | LWA,1s, d 85.5dB | These values are determined - and documented in accordance to EN12549:1999 |
| | A-weighted single-event sound pressure level | LpA, 1s, d 79.4dB | |
| VIBRATION Vibration characteristic value | | 3.2m/s ² These values are determined and documentedin accordance to ISO 8662-11 | |

FASTENERS APPLICABLE 15 Ga. Angled Finish Nails Length 32mm (1-1/4")65mm (2-1/2")Thickness 1.83mm (.072") → |



The Netherlands

Camerastraat 19, 1322 BB Almere Tel: +31-(0)36-546-9669 FAX: +31-(0)36-536-3985 Web:www.max-europe.com

e-mail:sales@max-europe.com

Dealer: